



FCC ID: RSNCMFLEX IC: 7784A - FLEX3

& DA

2G, 3G and 4G ready 5-Band cellular booster

## Product Number: Fantom (CA-VAT-100)

The first self-contained, -band booster designed as a cost-effective all-in-one cellular voice and data solution for large vessels, and capable of supporting 100 multiple users at the same time. It combines PCS and cellular dual-band with LTE and AWS frequencies for Verizon, AT&T and T-Mobile as a total 2G, 3G and 4G cellular booster solution.

This full-featured booster includes adjustable gain control and automatic shutdown for maximum flexibility. This booster requires one fifth the space and is a fraction of the cost compared to similar boosters with its capabilities. Ideal for locations with low cellular signal and/or requiring large coverage. Covers up to 80,000 square feet



Kit Includes: (pictured items) CVAT-100 Amplifier User Manual

Features:	Benefits:	
• Five Band	Works with AT&T, T-Moblie and Verizon 2G, 3G, & 4G Networks	
• 4G Compatible	Faster data Uploads and Downloads with No Buffering	
Adjustable Dials	Allows for Reception Optimization	
Reconfigurable 5-Band	> Easily Adjustable for Any Vessel or Building	IDEAL FO MARINE & RECREATIO VEHICLE
Tower Proximate Technology	Automatically Recognizes Signal Overload to Cell Towers	VENICLES
• Unique linear Design —	Supports Multi-Users (up to 100)	

## **Technical Specifiations**

🔀 Easy Set Up

Energy Efficient and Durable Increase Reception = MORE BARS

Frequency	Uplink: 1850-1910 Downlink: 1930-1990   Uplink: 824-849 Downlink: 869-894   Uplink: 698-716 Downlink: 728-746   Uplink: 776-787 Downlink: 746 -757   Uplink: 1710-1755 Downlink: 2110-2155	
Input Impedance	50 ohm	
Average Gain Maximum Gain	50 dB 50 dB	
VSWR	≤2.0	
Standard Supported	CDMA, GSM, UMTS, WCDMA, HSPA(+), EVDO, LTE and all other standard cell phone networks	
AC Power Transformer	Input AC110V, 60Hz; Output: DC19V	
Maximum RF Output Power	27 dBm with High Linearity	
Noise Figure	7dB	
Cable	LMR240 or LMR400 recommended	
RF connectors	N Female connectors on both ends	
PowerConsumption	<65W	
Dimensions (product)	14.5″ x 11″ x 3.5″	
Dimensions (box)	17.5" x 17.25" x 6"	
Weight (in box, without box)	24 lbs. (19.5 lbs.)	





6111 Shakespeare Road Columb www.shakespeare-marine.com